



# DESIGNED TO PERFORM.



- Lower operating costs World-class comfort and safety 3-year standard warranty on the vehicle 3-year anti-perforation warranty for cabin
  - Electro-deposited coating on load body for longer life Long service intervals (40,000 kms)

### **Technical specifications:**

Engine type H-series, 4-cylinder diesel engine with in-line fuel injection

pump (FIP)

Maximum power 120 HP @ 2400 RPM

Maximum torque 415 Nm @1400 RPM

Clutch 310 mm diameter, single plate dry type with hydraulic

actuation and clutch booster

Transmission 6-speed overdrive gearbox, FGR-6.93:1

Front axle Reverse Elliot, 'I'-section

Rear axle Fully floating, single reduction hypoid gear

Rear axle ratio 5.71:1

Frame 204 x 62 x 7 mm, ladder type with bolted construction

Steering Power assisted steering with tilt-able & telescopic adjustments

Cabin Day cabin with hydraulic tilt mechanism

Service brakes Full air, dual line, S-cam brake

Parking brakes Spring actuated pneumatic (rear only)

Tyres 8.25 X 20-16 PR: radial option

Fuel tank 208 ltrs (108 ltrs for 14ft)

Voltage 24 V electrical system with double layer protection

Battery capacity 2 X 12 V / 75 AH

GVW 12,900 kgs

Maximum speed in

top gear 85 kmph
Gradeability 19.96%

Height of load body

(FSD/DSD/HSD) 590 / 590 / 1105 mm

### **Major dimensions:**

Wheel base options (mm)	3400	3900	4500	4900
Loading span (ft)	14	17	20	22
Overall length with body (mm)	6422	7328	8163	8813
Turning diameter (mm)	11760	13360	15400	16760
Load body internal width(mm)	2105	2105	2135/2210	2210
Min. ground clearance (mm)	260			

**Colour options:** Casablanca white NP Brown

## **Major applications:**

- Construction (sand, blue metal) Cement Food grains
- Market load

# **Service offerings:**













No.1, Sardar Patel Road, Guindy, Chennai - 600032.

Ph. no: 044-2220 6000 Fax: 044-2220 6001

Website: www.ashokleyland.com | www.leylandboss.com

E-mail: reachus@ashokleyland.com | CIN: L34101TN1948PLC000105

Specifications are subject to change due to continuous improvements and are for reference only.